

Hose-Master

Single Hose, General Purpose Reels

Standard Features

- 300 PSI standard rating, ratings to 1500 PSI available.
- 1. Optional Ball Stop
- 2. Standard Roller Guide accommodates a variety of mounting configurations.
- 3. Fluid Path/ Main Shaft also available in stainless steel.
- 4. Safetychange® Spring Motor makes replacement safe and easy.
- 5. Welded, all steel frame for maximum strength.
- 6. Optional 340° Pivot Base (not shown).
- Ratchet Lock w/Disengagement STANDARD.



Air Hose Reels

Lift

STANDARD HOSE SIZE	FEET OF HOSE					
	20	30	40	50	60	70
1/4 X 5/8	HM141-4-P3	HM143-4-P1	HM143-4-P2	HM197-4-P2	HM197-4-P3	HM197-4-P4
3/8 X 3/4	HM141-6-P4	HM142-6-P3	HM197-6-P2	HM197-6-P3	HM197-6-P4	HM197-6-P5
1/2 X 7/8	HM142-8-P3	HM197-8-P4	HM194-8-P2			

Stretch (capacities based on 10% sag)

STANDARD HOSE SIZE	FEET OF HOSE					
	20	30	40	50	60	70
1/4 X 5/8	HM141-4-P4	HM142-4-P2	HM143-4-P2	HM197-4-P2	HM197-4-P3	HM197-4-P4
3/8 X 3/4	HM142-6-P2	HM142-6-P3	HM197-6-P2	HM197-6-P3	HM197-6-P4	HM194-6-P2
1/2 X 7/8	HM142-8-P3	HM194-8-P1	HM194-8-P2			

Retrieve (capacities based on 3 ft. mounting height)

STANDARD HOSE SIZE	FEET OF HOSE					
	20	30	40	50	60	70
1/4 X 5/8	HM142-4-P2	HM142-4-P3	HM143-4-P2	HM197-4-P3	HM197-4-P4	HM194-4-P1
3/8 X 3/4	HM142-6-P2	HM142-6-P3	HM197-6-P3	HM197-6-P4	HM197-6-P5	HM194-6-P2
1/2 X 7/8	HM143-8-P3	HM195-8-P2	HM195-8-P3			

Lift

Liquid Hose Reels

STANDARD HOSE SIZE	FEET OF HOSE					
	20	30	40	50	60	70
1/4 X 5/8	HM141-4-P4	HM142-4-P2	HM143-4-P2	HM197-4-P2	HM197-4-P3	HM197-4-P4
3/8 X 3/4	HM142-6-P2	HM142-6-P3	HM197-6-P2	HM197-6-P3	HM197-6-P4	HM194-6-P2
1/2 X 7/8	HM142-8-P3	HM194-8-P1	HM194-8-P2			

Stretch (capacities based on 10% sag)

STANDARD HOSE SIZE	FEET OF HOSE					
	20	30	40	50	60	70
1/4 X 5/8	HM141-4-P4	HM142-4-P2	HM143-4-P2	HM197-4-P2	HM197-4-P3	HM197-4-P4
3/8 X 3/4	HM142-6-P2	HM142-6-P3	HM197-6-P3	HM197-6-P4	HM194-6-P1	HM194-6-P2
1/2 X 7/8	HM142-8-P4	HM194-8-P1	HM194-8-P2			

Retrieve (capacities based on 3 ft. mounting height)

STANDARD HOSE SIZE	FEET OF HOSE					
	20	30	40	50	60	70
1/4 X 5/8	HM142-4-P2	HM142-4-P3	HM142-4-P2	HM197-4-P3	HM197-4-P4	HM194-4-P1
3/8 X 3/4	HM142-6-P2	HM142-6-P3	HM197-6-P3	HM197-6-P4	HM197-6-P5	HM194-6-P2
1/2 X 7/8	HM143-8-P4	HM195-8-P2	HM195-8-P3			

Options- Add as suffix to model numbers above: **C2** = Ball Stop **S** = Pivot Base **SS** = Stainless Steel Fluid Path



K-Reels

Dual Hose, Hydraulic Reels

Standard Features

- 3000 PSI standard swivel joint rating.
- 1. Dual port swivel joint removes easily when replacing seal.
- 2. Hose connections readily accessible.
- 3. Welded, all steel frame for maximum strength.
- Safetychange® Spring Motor makes replacement safe and easy.
- Optional Ratchet Lock.
- Pre-lubricated, sealed ball bearings.



Lift

FEET OF HOSE	STANDARD HOSE SIZES*			
	1/4" I.D.	3/8" I.D.	1/2" I.D.	3/4" I.D.
10	K18351-4-10	K21351-6-10	K18751-8-1	K241001-12-1
15	K18351-4-10	K21751-6-1	K21751-8-1	K241001-12-2
20	K21751-4-1	K21751-6-1	K21751-8-1	K281001-12-6
25	K21751-4-1	K24751-6-1	K24751-8-2	K32753-12-4
30	K24751-4-1	K24751-6-1	K28751-8-5	K32753-12-4
35	K24751-4-1	K28751-6-3	K281001-8-1	K32753-12-4
40	K28751-4-1	K28751-6-3	K321001-8-1	
45	K28751-4-1	K281001-6-1	K321001-8-1	
50	K28751-4-1	K281001-6-1	K321001-8-1	
55	K28751-4-1	K321001-6-1		
60	K321001-4-1	K321001-6-1		
65	K321001-4-1	K321001-6-1		
70	K321001-4-1			
75	K32802-4-1			
80	K32802-4-1			

Stretch (capacities based on 6% sag)

FEET OF HOSE	STANDARD HOSE SIZES*			
	1/4" I.D.	3/8" I.D.	1/2" I.D.	3/4" I.D.
10	K18751-4-1	K18751-6-1	K18751-8-3	K241001-12-5
15	K18751-4-1	K21751-6-2	K21751-8-4	K241001-12-5
20	K21751-4-1	K21751-6-2	K21751-8-4	K28753-12-3
25	K21751-4-1	K24751-6-5	K241001-8-1	K32753-12-8
30	K24751-4-1	K24751-6-5	K281001-8-5	K32754-12-4
35	K24751-4-1	K281001-6-1	K281001-8-3	K32754-12-4
40	K281001-4-1	K281001-6-1	K32752-8-3	
45	K281001-4-1	K281001-6-1	K32752-8-3	
50	K281001-4-1	K281001-6-1	K32753-8-1	
55	K281001-4-1	K32752-6-1		
60	K321001-4-1	K32753-6-1		
65	K321001-4-1	K32753-6-1		
70	K321001-4-1			
75	K32802-4-7			
80	K32802-4-7			

Charts above based on SAE100R2 two wire braid hose. Consult factory if vinyl hose is to be used. Weights shown below for single hose without fluid.

I.D.	MAX O.D.	WEIGHT PER FOOT
0.250"	0.580"	0.330 lbs.
0.375"	0.840"	0.450 lbs.
0.500"	0.970"	0.560 lbs.
0.750"	1.250"	0.800 lbs.



GLEASON K-REEL installed on a hoist.

