

This guide provides specifications for Unitronics model V350-35-R2. General features include: 12 pnp/npn Digital, including 2 Analog, 3 HSC/Shaft-encoder Inputs, 6 Relay Outputs, I/O Expansion Port, built-in RS232/RS485. Available by separate order: Ethernet, additional RS232/RS485, CANbus.

### Technical Specifications

---

#### Power Supply

|                          |  |
|--------------------------|--|
| Input voltage            | 24VDC  |
| Permissible range        | 20.4VDC to 28.8VDC with less than 10% ripple |
| Max. current consumption | See Note 1                                   |
| npn inputs               | 250mA@24VDC                                  |
| pnp inputs               | 160mA@24VDC                                  |

#### Notes:

1. To calculate the actual power consumption, subtract the current for each unused element from the maximum current consumption value according to the values below:

| Backlight | Ethernet card | Relay Outputs (per output) |
|-----------|---------------|----------------------------|
| 20mA      | 35mA          | 8mA                        |

---

#### Digital Inputs

|                       |   |
|-----------------------|---|
| Number of inputs      | 12. See Note 2  |
| Input type            | See Note 2  |
| Galvanic isolation    | None  |
| Nominal input voltage | 24VDC   |
| Input voltage         |   |
| pnp (source)          | 0-5VDC for Logic 0<br>17-28.8VDC for Logic 1                                |
| npn (sink)            | 17-28.8VDC for Logic 0<br>0-5VDC for Logic 1                                |
| Input current         | 8mA@24VDC   |
| Input impedance       | 3K  |
| Response time         | 10mSec typical, when used as normal digital inputs                          |
| Input cable length    | Up to 100 meters, unshielded  |
| High speed inputs     | Specifications below apply when wired as HSC / shaft-encoder.<br>See Note 2 |
| Resolution            | 32-bit  |
| Frequency             | 10kHz maximum   |
| Minimum pulse width   | 40µs  |

**Notes:**

2. This model comprises a total of 12 inputs. Input functionality can be adapted as follows:  
All 12 inputs may be used as digital inputs. They may be wired, in a group, and set to either npn or prp via a single jumper.

In addition, according to jumper settings and appropriate wiring:

- Inputs 10 and 11 can function as **either** digital or analog inputs.
- Inputs 0, 2, and 4 can function as, high-speed counters, as part of a shaft-encoder, or as normal digital inputs.
- Inputs 1, 3, and 5 can function as either counter reset, as part of a shaft-encoder, or as normal digital inputs.

**Digital Outputs**

|                    |  |
|--------------------|--|
| Number of outputs  | 6 relay  |
| Output type        | SPST-NO (Form A)   |
| Isolation          | By relay   |
| Type of relay      | Panasonic JQ1AP-24V or compatible  |
| Output current     | 5A maximum (resistive load)  |
| Rated voltage      | 250VAC / 30VDC   |
| Minimum load       | 1mA@5VDC   |
| Life expectancy    | 50k operations at maximum load   |
| Response time      | 10mS (typical)   |
| Contact protection | External precautions required (see Increasing Contact Life Span in the product's Installation Guide) |

**Analog Inputs**

|                            |  |         |
|----------------------------|--|---------|
| Number of inputs           | 2, according to wiring as described above in Note 2                                    |         |
| Input type                 | Multi-range inputs: 0-10V, 0-20mA, 4-20mA  |         |
| Input range                | 0-20mA, 4-20mA   | 0-10VDC |
| Input impedance            | 243Ω   | >150KΩ  |
| Maximum input rating       | 25mA, 6V   | 15 V    |
| Galvanic isolation         | None   |         |
| Conversion method          | Successive approximation   |         |
| Resolution (except 4-20mA) | 10-bit (1024 units)  |         |
| Resolution (at 4-20mA)     | 204 to 1023 (820 units)  |         |
| Conversion time            | Synchronized to cycle time   |         |
| Precision                  | 0.9%   |         |
| Status indication          | Yes – if an analog input deviates above the permissible range, its value will be 1024. |         |

**Graphic Display Screen**

|                        |   |
|------------------------|---|
| LCD Type               | TFT, LCD display  |
| Illumination backlight | White LED, software-controlled                                      |
| Display resolution     | 320 x 240 pixels  |
| Viewing area           | 3.5"  |
| Colors                 | 256   |
| Touchscreen            | Resistive, analog   |
| 'Touch' indication     | Via buzzer  |
| Screen brightness      | Via software (Store value to SI 9).                                 |
| Keypad                 | Displays virtual keyboard when the application requires data entry. |

**Keys**

|                |   |
|----------------|---|
| Number of keys | 5 programmable function keys  |
| Key type       | Metal dome, sealed membrane switch  |
| Slides         | Slides may be installed in the operating panel faceplate to custom-label the keys. Refer to V350 Keypad Slides.pdf.<br>Two sets of slides are supplied with the controller: one set of arrow keys, and one blank set. |

**Program**

|                   |   |        |                        |
|-------------------|---|--------|------------------------|
| Memory size       | Application Logic – 1Mb, Images – 3Mb, Fonts – 512 Kb   |        |                        |
| Operand type      | Quantity  | Symbol | Value                  |
| Memory Bits       | 8192  | MB     | Bit (coil)             |
| Memory Integers   | 4096  | MI     | 16-bit signed/unsigned |
| Long Integers     | 512   | ML     | 32-bit signed/unsigned |
| Double Word       | 256   | DW     | 32-bit unsigned        |
| Memory Floats     | 64  | MF     | 32-bit signed/unsigned |
| Timers            | 384   | T      | 32-bit                 |
| Counters          | 32  | C      | 16-bit                 |
| Data Tables       | 120K dynamic data (recipe parameters, datalogs, etc.),<br>192K fixed data (read-only data, ingredient names, etc) |        |                        |
| HMI displays      | Up to 1024  |        |                        |
| Program scan time | 15µS per 1kb of typical application   |        |                        |

**Communication Ports**

|                    |   |
|--------------------|---|
| Port 1             | 1 channel, RS232/RS485. See Note 3                |
| Galvanic isolation | No  |
| Baud rate          | 300 to 115200 bps                                 |
| RS232              |   |
| Input voltage      | ±20VDC absolute maximum                           |
| Cable length       | 15m maximum (50 feet)                             |
| RS485              |   |
| Input voltage      | -7 to +12VDC differential maximum                 |
| Cable type         | Shielded twisted pair, in compliance with EIA 485 |
| Cable length       | 1200m maximum (4000 feet)                         |
| Nodes              | Up to 32  |
| Port 2 (optional)  | See Note 4  |
| CANbus (optional)  | See Note 4  |

**Notes:**

- This model is supplied with a serial port: RS232/RS485 (Port 1). The standard is set to either RS232 or RS485 according to jumper settings. Refer to the product's Installation Guide.
- The user may order and install one or both of the following modules:
  - An additional port (Port 2). Available port types: RS232/RS485 isolated/non-isolated, Ethernet
  - A CANbus port
Port module documentation is available on the Unitronics website.

**I/O Expansion Port**

Expansion modules Via adapter, use up to 8 I/O Expansion Modules comprising up to 128 additional I/Os. Number of I/Os and types vary according to module.

**Miscellaneous**

Clock (RTC) Real-time clock functions (date and time).  
 Battery back-up 7 years typical at 25°C, battery back-up for RTC and system data, including variable data  
 Battery replacement Yes. Coin-type 3V, lithium battery, CR2450

**Dimensions**

Size 109 x 114.1 x 68mm (4.29 x 4.49 x 2.67"). See Note 5  
 Weight 227g (8 oz)

**Notes:**

5. For exact dimensions, refer to the product's Installation Guide.

**Environment**

Operational temperature 0 to 50°C (32 to 122°F)  
 Storage temperature -20 to 60°C (-4 to 140°F)  
 Relative Humidity (RH) 10% to 95% (non-condensing)  
 Mounting method Panel mounted (IP65/NEMA4X)  
 DIN-rail mounted (IP20/NEMA1)

The information in this document reflects products at the date of printing. Unitronics reserves the right, subject to all applicable laws, at any time, at its sole discretion, and without notice, to discontinue or change the features, designs, materials and other specifications of its products, and to either permanently or temporarily withdraw any of the forgoing from the market.

All information in this document is provided "as is" without warranty of any kind, either expressed or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose, or non-infringement. Unitronics assumes no responsibility for errors or omissions in the information presented in this document. In no event shall Unitronics be liable for any special, incidental, indirect or consequential damages of any kind, or any damages whatsoever arising out of or in connection with the use or performance of this information.

The tradenames, trademarks, logos and service marks presented in this document, including their design, are the property of Unitronics (1989) (R<sup>g</sup>) Ltd. or other third parties and you are not permitted to use them without the prior written consent of Unitronics or such third party as may own them.